

RG-RAP2260(H)

Wi-Fi 6 AX6000 High-density Multi-G Ceiling Access Point

DATASHEET



Highlights

- Build ultra-high performance Wi-Fi with 5.95Gbps throughput.
- Client connections over 500, higher practical performance as well.
- Boost Internet speed with 5Gbps uplink for the future.
- Easily install extra AP with Reyee Mesh technology.
- Support standalone captive portal, easy to enable Wi-Fi authentication.

Highlight Features

Build Ultra-fast and High-density Wi-Fi 6 Network for the Future

Interface Installation



WIFI 6 AX6000 Wi-Fi 6 4x4 MIMO 4 x 4 MU-MIMO Dual 2.5GE Wired Uplink Reye Mesh Technology Free Cloud Management

Build Ultra-fast Wi-Fi Network for the Future

Interface Installation



WIFI 6 AX6000 Wi-Fi 6 4x4 MIMO 4 x 4 MU-MIMO Dual 2.5GE Wired Uplink Reye Mesh Technology Free Cloud Management



Better Multi-User Experience in High-Density Scenarios

Performance upgraded, support client connections over 500.



Users 500 4x4 MIMO 2.4G 5G

Highlight Features



Highlight Features

More Flexiable Wi-Fi Authentication


Support standalone captive portal, easy to enable Wi-Fi authentication based on Ruijie Cloud only.*



* Access point standalone portal authentication will be supported in Q2 2023 through new firmware.

Cloud, Make Your Business Easy

- Self-organizing network
- Centralized network management
- Scenario based configuration
- Cloud portal authentication
- Remote monitoring and maintenance



The Ruijie Cloud management interface on the tablet displays the following data:

- Overview:** 10 Sites, 14 Users, 0 Alerts, 3 Events.
- Registered Device Distribution:** A map showing the distribution of devices across various locations.
- Channel Distribution and Usage:** A bar chart showing channel usage across different sites.
- WiFi User Equipment:** A bar chart showing the distribution of user equipment types.

Specifications

Basic Feature	
Wi-Fi Standards	Wi-Fi 6 (IEEE 802.11ax) Wi-Fi 5 (IEEE 802.11ac Wave 2) Wi-Fi 4 (IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g
MIMO	2.4GHz, 4×4, MU-MIMO 5GHz, 4×4, MU-MIMO
Max. Wi-Fi Speed	2.4GHz: 1148Mbps 5GHz: 4804Mbps
Antenna	8
Antenna Type	Built-In Omnidirectional
Antenna Gain	2.4GHz: 3dBi 5 GHz: 4dBi
Transmit Power	EIRP: ≤35dBm (2.4GHz) ≤36dBm (5GHz) country-specific restrictions apply Myanmar: 2400 MHz~2483.5 MHz ≤ 20 dBm 5150 MHz~5350 MHz ≤ 23 dBm 5470 MHz~5850 MHz ≤ 25 dBm Thailand: 2400 MHz~2483.5 MHz ≤ 20 dBm 5150 MHz~5350 MHz ≤ 23 dBm 5470 MHz~5725 MHz ≤ 25 dBm 5725 MHz~5850 MHz ≤ 30 dBm Egypt: 2400 MHz~2483.5 MHz ≤ 20 dBm (EIRP) 5150 MHz~5350 MHz ≤ 20 dBm (EIRP)
Fixed Ports	2 x 100/1000/2500 Base-T ports 1 × Reset button 1 x DC port
Max. Clients	512
Recommended Clients	130
Max. SSIDs	8

Specifications

Basic Feature

Recommended Wi-Fi Coverage Radius	2.4GHz: 40 meters 5GHz: 70 meters The Wi-Fi coverage is related to the installation environment of the access point.
Max. Wi-Fi Coverage Radius	150 meters
Operation Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.4835 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply Egypt: 802.11b/g/n: 2.4 GHz ~ 2.4835 GHz 802.11a/n/ac: 5.150 GHz ~ 5.350 GHz

Software Feature

WLAN Basic Features	
Power Adjustment	✓
Frequency Bandwidth	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz
Roaming	Layer 2 roaming Layer 3 roaming
OFDMA	✓
Beamforming	✓
WMM	✓
Radar Signal Detection and Frequency Hopping (DFS)	✓
WLAN Security	
Max Wi-Fi Password Length	16 Digits
Security Mode	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
Blacklist and Whitelist	✓
Enhanced User Experience	
Wi-Fi Optimization	✓

Specifications

Software Feature	
STA Limit	✓
Removing Low-RSSI STAs	✓
Adjusting Sending Rate of Beacon and Probe Response	✓
Syslog Recording Why Users Lose Connection	✓
Auto Channel and Power Adjustment on Cloud	✓
RSSI Threshold for STA Access	✓
Load Balancing	✓
Networks	
Network Access Mode	PPPoE Client DHCP Client Static IP
VLAN	✓
DHCP Server	✓
System	
Cloud Management	✓
APP Management	✓
APP Upgrade	✓
APP Restart	✓
Scheduled Restart	✓
Default Access/Password	10.44.77.253 No Password Required by Default
Local Upgrade	✓
Online Upgrade	✓

Specifications


System	
Dual-bin Backup	✓
Factory Reset	✓
Language	Chinese English
System Log	✓
Diagnostics	✓
Network Check	✓
Physical	
LED Indicator	1 × System LED indicator
Buttons	1 × Reset button
Dimensions (W × D × H)	230 mm x 230 mm x 49.5 mm (Without Mounting Bracket)
Weight	≤ 1.80 kg (Without Mounting Bracket)
DC Port Dimensions	Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm Length: 10 mm
Installation	Ceiling-Mountable
Mounting Bracket Dimensions (W × D × H)	120 mm x 120 mm x 8.7 mm
Mounting Hole Pattern	53 mm x 53 mm
Mounting Hole Diameter	6.5 mm
Pole Diameter	NA
Power Supplies	IEEE 802.3bt PoE DC 48V/1A
Power Consumption	≤ 40W
PoE Power Budget	NA

Specifications


Physical	
Environmental	
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Operating Humidity	5% to 95% Noncondensing
Storage Humidity	5% to 95% Noncondensing
IP(Ingress Protection)	NA
Port Surge	4kV
MTBF	>400000H

Antenna Schematic

2.4GHz



5GHz



Package Contents

Package Information	RG-RAP2260(H)
Access Point	1
User Manual	1
Certificate of Quality	1
Screws and Wall Anchors	4
Mounting Bracket	1
Key to Security Lock	1
Package Weight	1.79 kg
Package Dimension (w x d x h)	292mm x 277 mm x 81 mm

Ruijie | Rcycc

 **R**edefine your easy network

Copyright ©2000-2022 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd
Floor 11, East Wing, Zhongyipengao Plaza,
No.29 Fuxing Road, Haidian District, Beijing China
Website: <https://www.ruijienetworks.com>